



FERREX

The settings below follow testing by SCS Spreader & Sprayer Testing Ltd.

They should be regarded as indicative and users should follow appropriate calibration regimes for their machines and allow for field conditions in order to achieve a good spread.

Machine	Disc / Vane type	Spreader height/tilt	Rate Kg/ha	Disc Speed	Spread width	Spread setting
Bullock T24	275mm	110cm 0*	6	No.12	12m	Centre
		110cm 0*	6	No.15	18m	Centre
		110cm 0*	6	No.30	24m	Centre
		110cm 0*	6	No.30	28m	Centre
Logic TFS80P	3 vane deep	100cm 0*	6	3000	12m	5.5
		100cm 0*	6	3000	18m	10
Spaldings Lehner Super Vario	2 vane vario	100cm 0*	6	3000	12m	2 & 3
		100cm 0*	6	3000	15m	2 & 3
Stocks Ag Fan Jet Pro 65	2 vane	110cm 0*	6	No.6	12m	90
		110cm 0*	6	No.12	18m	90
		110cm 0*	6	No.12	20m	90
Stocks Ag Fan Jet Duo	2 long 2 short	150cm 0*	6	No.8	12m	105
		150cm 0*	6	No.10	18m	105
		150cm 0*	6	No.12	24m	105
		250cm 0*	6	No.12	30m	105

Head Office

4c Archway House, The Lanterns, Melbourn Street
Royston, United Kingdom. SG8 7BX.

T: +44 (0)1763 212100 F: +44 (0)1763 212101

www.sipcamuk.co.uk

Always Read The Label. Use Pesticides Safely

'Ferrex' contains Ferric Phosphate.